

Dependable print partner

Quietly effective, the RICOH P 501/P 501TL Printers respond efficiently to workgroup black and white print requirements — producing immaculately presented documents, quickly and reliably.

Cutting-edge LED technology:

- Powerful Intel® processor
- First page ready in under 5 seconds
- Fast 45 ppm (Letter)/43 ppm (A4) throughput
- 1,200 x 1,200 dpi quality

Ricoh's innovative LED technology delivers significant advances in speed, quality and reliability. With their powerful Intel® processor, the RICOH P 501/P 501TL quickly process even the most complex jobs — printing pitch-perfect 1,200 x 1,200 dpi black and white output at a productive 45 pages per minute. With their high duty rating, they reliably meet peaks in demand.

Compact and quietly effective:

- Space-saving design
- Up to four paper trays
- Automatic tray switching
- Extensive media support



As well as boasting class-leading specifications, the RICOH P 501/P 501TL are surprisingly easy to live with. Their compact design and quiet operation ensure that they can be placed on a desk or under a counter, within easy reach. The optional paper trays enhance productivity. Envelopes and letterhead can be fed automatically. In addition, with the printer switching from one tray to another, you need never run out of paper. With a low investment cost, these printers promise an exceptional return.

Mobile and cloud-enabled printing:

- PCL and PS3 print drivers
- Mobile printing solution
- AirPrint™

With their PCL and PS3 print drivers, the RICOH P 501/P 501TL are fully in sync with all IT requirements. To facilitate mobile working, they also support AirPrint™. There is no need to fire up a PC or join a print network; documents can be printed directly to the printer from iOS™ and Android™ devices. In addition to everyday letters and reports, the RICOH P 501TL, which has a label enhanced paper path, can be used to print wristbands and labels.



RICOH P 501/P 501TL

MAIN SPECIFICATIONS

GENERAL

Warm-up time 13 seconds

First output speed 4.3 seconds (A4 / LT SEF)

 Memory: standard
 2 GB

 HDD: option
 320 GB

 Duty cycle
 150K

Dimensions: W x D x H 14.76" x 16.22" x 12.24" (375 x 412 x 311 mm)

 Weight: basic model
 42.5 lbs. (19.3 kg)

 Power source
 120-127V/12A 60Hz

PRINTER (STANDARD)

Printer language: standard PCL5e, PCL6, PostScript® 3™ (emulation), PDF direct (emulation)

Printer language: option IPDS, Genuine Adobe® PostScript® 3™, PDF Direct from Adobe®

Print resolution: maximum 1,200 x 1,200 dpi

Fonts: PCL 13 international fonts, 80 Roman fonts Fonts: PS3 (emulation) 13 international fonts, 80 Roman fonts

 Network interface: standard
 USB 2.0, Ethernet 10 base-TX/1000 base-TX/1000 base-TX, USB 2.0 Host

 Network interface: option
 Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port)

 Mobile printing capability
 Apple AirPrint*, Mopria*, NFC, RICOH Smart Device Connector

Network protocol TCP/IP (IP v4, IP v6)

Windows® environments Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016

Mac OS environments Macintosh OS X v10.10 or later SAP® environments SAP® R/3®, SAP® S/4®

Other supported environments NDPS Gateway, AS/400® using OS/400 Host Print Transform, Device Option Utility (Citrix), Linux environment, IBM iSeries

PAPER HANDLING

Paper input: standard 500 sheets
Paper input: maximum 2,100 sheets
Paper input: Bypass tray 100 sheets

Paper weight Paper tray(s): 14 - 58 lb. Bond (52 - 220 g/m²)
Optional paper tray(s): 14 - 58 lb. Bond (52 - 220 g/m²)

Optional paper tray(s): 14 - 58 lb. Bond (52 - 220 g/m²) Bypass tray: 14 - 68 lb. Bond (52 - 220 g/m²)

Bypass tray: 14 - 68 lb. Bond (52 - 220 g/m²

Paper types Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP

ENVIRONMENTAL SUSTAINABILITY

 Power consumption: Maximum (W)
 Less than 1,360 W

 Power consumption: TEC¹
 0.50 kWh

 ENERGY STAR®
 Certified

 EPEAT®
 Gold Rated*

Gold Rated*

* EPEAT Gold rating is applicable only in the USA.

PAPER HANDLING OPTIONS

 1x 250-sheet Paper Tray (PB 1110)
 Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6); Paper weight: 14-58 lb. Bond (52-220 g/m²)

 1x 500-sheet Paper Tray (PB 1120)
 Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5); Paper weight: 14-58 lb. Bond (52-220 g/m²)

 1x 250-sheet Paper Tray (PB1110TL)
 Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6); Paper weight: 14-58 lb. Bond (52-220 g/m²)

 1x 500-sheet Paper Tray (PB1120TL)
 Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5); Paper weight: 14-58 lb. Bond (52-220 g/m²)

 $^{^{\}rm 1}$ TEC value is measured based on the ENERGY STAR Ver. 3.0 test method

RICOH P 501/P 501TL

MAIN SPECIFICATIONS

OTHER OPTIONS

Caster Table Type M34, VM Card Type P18, PostScript3 Unit Type P18, IPDS Unit Type P18, Hard Disk Drive Option Type P18, Medium Cabinet Type P, Tall Cabinet Type P, Tall Cabinet Type P0, IEEE802.11 Interface Unit Type M24, ESP XG-PCS-15D & ESP S1 Power Filter

CONSUMABLES

Toner P 501H 14,000 prints Drum Unit P 501 40,000 prints Maintenance Kit P 501 120,000 prints

Consumable yield measuring method ISO/IEC 19752

Some options may not be available at the time of market release

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

300 Eagleview Boulevard Exton, PA 19341



1-800-63-RICOH



www.ricoh-usa.com

