

A4 Color Printer

P C375

Printer Copier Scanner Fax



P C375



32-ppm

RICOH P C375

MAIN SPECIFICATIONS

GENERAL

| | |
|-------------------------------|---|
| Warm-up time | Less than 32 seconds |
| Recovery time | 10 seconds |
| First print time (B/W) | 4.1 seconds |
| First print time (Full Color) | 5.3 seconds |
| Continuous output speed | 32 ppm / 32 ppm (simplex); 16 ppm / 16 ppm (duplex) |
| Memory/Storage | 2GB RAM/ 32GB eMMC (Standard) |
| Weight | 25 kg / 55.1 lbs |
| Dimensions: W x D x H | 16.1" x 16.9" x 14.4" (410 x 429 x 360 mm) |
| Power source | 120V-127V, 60Hz |

PRINTER

| | |
|-----------------------------|---|
| CPU | QB6640-23UF, 1.2GHz |
| Printer language: | PCL6, PostScript®3™ Emulation, PDF Direct Print Emulation |
| Printer language: | Genuine Adobe® PostScript®3™, Adobe® PDF Direct Print |
| Print resolution: | Up to 1,200 x 1,200 dpi (1-bit) |
| Network interface: standard | 10BASE-T/100BASE-TX/1000BASE-T (Gigabit Ethernet), USB Host Type A-1 port (for service use only), USB Device Type B-1 port, SD Card slot, USB Host Type A-1 port (for Media Direct Print) |
| Network interface: optional | Wireless LAN, (IEEE 802.11 a/b/g/n/ac) |
| Network protocols | TCP/IP (IPv4, IPv6) |
| Mobile printing capability | AirPrint, Mopria®, RICOH Smart Device Connector |
| Fonts: standard | 80 Roman fonts + 13 International fonts |
| Fonts: PS3 optional | 136 Roman fonts (with Genuine Adobe PostScript®3™ option) |
| Windows® environments | Windows 10 (32-/64-bit), 11, Server 2016, Server 2019, Server 2022 |
| MacOS environments | MacOS 11 and later |
| SAP® environments | SAP R/3, SAP S/4 (optional Unicode font package required) |
| Citrix environments | Citrix XenDesktop 7.0/7.1, Citrix XenApp 7.5 and later |

PAPER HANDLING

| | |
|-----------------------|--|
| Supported paper size | Standard Paper Tray: Up to 8.5" x 11" / A4, Optional Paper Tray: Up to 8.5" x 14", Bypass: Up to Up to 8.5" x 14", Envelopes |
| Paper input: standard | 300 sheets (250-sheet tray plus 50-sheet bypass) |
| Paper input: maximum | 1300 sheets (250-sheet tray plus 500-sheet optional paper tray and 50-sheet bypass) |
| Paper output | 200 sheets (face down) |
| Paper weight | Standard Trays: 16 - 53 lb. Bond /110 lb. Index (60 - 200 g/m ²), Bypass Tray: 16 - 53 lb. Bond Index (60 - 200 g/m ²), Duplex Unit: 16 - 43 lb. Bond /90 lb. Index (60 - 163 g/m ²) |
| Paper types | Plain Paper, Recycled Paper, Colored Paper, Special Paper 1-3, Letterhead, Preprinted Paper, Bond Paper, Cardstock, Label Paper, Backing Paper, Envelopes, Coated Paper |

SECURITY FEATURES

| | |
|--|---|
| Prevent unauthorized access to device | 802.1x wired authentication, IEEE 802.11 security (WEP, WPA, WPA2, WPA3), quota setting/account limit, user authentication—Windows, LDAP via Kerberos, basic, user code authentication, Wi-Fi Protected Setup (WPS) support |
| Prevent unauthorized access to network | IP filtering—access control, IPsec communication, network protocol on/off, Secure Sockets Layer (SSL) communication, Transport Layer Security (TLS 1.3), network user authentication, SNMPv3 |
| Protection of confidential information | Machine data encryption, authentication password encryption, compulsory security stamp, encrypted secure print |
| Protection of latent data | Erase All Memory function—to overwrite drive and NVRAM at machine end-of life |

ENVIRONMENTAL FEATURES

| | |
|-----------------------------------|---------------------------|
| Power consumption: | Maximum less than 1,500 W |
| Power consumption: ready/sleep | 120 W/0.53 W |
| Typical Energy Consumption (TEC)* | 0.29 kWh/week |

* A reference value based on the ENERGY STAR Ver.3.0 test method.

CONSUMABLES

| | |
|------------------------------|--|
| Toner (black)* | Print Cartridge Black P C375H: 13,500 pages |
| Toner (cyan/magenta/yellow)* | Print Cartridge Cyan P C375H, Print Cartridge Magenta P C375H, Print Cartridge Yellow P C375H: 10,000 pages each |
| Waste Toner Bottle** | Waste Toner Bottle IM C320: 11,000 pages |
| Imaging Unit (black)** | Black Drum Unit M C320: 60,000 pages |
| Imaging Unit (color)** | Color Drum Unit M C320: 48,000 pages |
| Transfer Unit** | Transfer Unit M C320: 100,000 pages |

*Declared toner yield in accordance with ISO/IEC 19798; **Yield based on 5% coverage at 3 pages/job.

PAPER SUPPLY OPTIONS

500-Sheet Paper Feed Unit PB1210, Low Cabinet Type A9, High Cabinet Type A10

OTHER OPTIONS

IEEE 802.11a/b/g/n/ac Interface Unit Type M57, PostScript®3™ Unit Type P24, Unicode font package for SAP

This device does not support PoE (Power over Ethernet) and should not be connected to a PoE hub. Connecting to a PoE hub could cause damage and void warranty coverage.

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.



RICOH
imagine. change.

Ricoh USA, Inc., 300 Eagleview Boulevard, Exton, PA 19341, 1-800-63-RICOH

©2024, Ricoh USA, Inc. All rights reserved. Ricoh® and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.